



## Highlights

- 3 Level Online UPS
- Industrial Design
- Microprocessor Control
- Transformer-free Design
- IGBT PWM Controlled
- Input Power Factor Correction
- High Output Power Factor
- Wide Input Voltage
- Converter Mode Available
- ECO Mode for Energy Saving
- Generator Compatible
- SNMP, RS-232, Modbus
- Comprehensive Display
- Up to 8 pcs N+1 Parallel Operation
- Soft Start Capacity
- Maintenance and Automatic Bypass
- 500 pcs Events Log
- 2 Years Warranty

## Savior Three-Phase Online UPS 250 - 800 kVA Technical Specifications

GENERAL					
Capacity	250 kVA	300 kVA	400 kVA	600 kVA	800 kVA
Power Factor	0.9 or 1.0				
Technology	3 Level Online UPS with DSP Control				
INPUT					
Voltage	380/400/415 Vac (or 208/480/600 Vac) ±15%				
Frequency	50 Hz / 60 Hz ±10%				
THDi	≤ 3% at Full Load				
Input Power Factor	≥0.99 at Nominal Voltage and Full Load				
OUTPUT					
Output Voltage	380/400/415 Vac (or 208/480/600 Vac) ±1%				
Bypass Voltage	380/400/415 Vac (or 208/480/600 Vac) ±15%				
Crest Factor	3:1 at Full Load				
Transfer Time	0 ms (from battery)				
THDv	<2% (at linear full load)				
Waveform	Pure Sinewave				
Overload Operation	100%-125% for 12 min, 125%-150% for 90 Sec, >150% Transfer to Bypass				
Efficiency	95% at Full Load, >98% at Eco Mode				
Protection	Short Circuit, Over Load, Battery Fuse, Bypass, Over Temperature Protections				
BATTERY					
Battery Qty 0.8 Model	60 pcs (± 30) Batteries				
Battery Qty 1.0 Model	60 pcs (± 30) Batteries				
Protection	Battery Deep Discharge Protection				
Battery Space	External Battery Cabinet				
Auto Battery Test	Manual and Automatic Battery Tests				
DISPLAY AND ALARMS					
Display	4x20 LCD Panel, 6" Touchscreen Panel (Optional)				
Event Logs	500 Events Recorded with Time and Date				
Indicators	Crest Factor, Volt, Current, Frequency, PF, Service Time				
Displayed Parameters	Input Voltage/Frequency, Output Voltage, Power, Output Current/Frequency, Battery Status, Load Status, Alarm Code, EPO and Fault Codes				
Communication	RS232 or RS485 Modbus (Standard), Dry Contact and SNMP (Optional)				
SAFETY and STANDARDS					
Standards	IEC/EN62040-1, IEC/EN60950-1, ISO 9001, CE				
EMC	EN/IEC 62040-2, EN/IEC 62040-3				
ENVIRONMENT					
Heat and Humidity	-10 C° / + 60 C°, 0 - 90% (non-condensing)				
Noise Level	Less than 65 dB at 1 mt				
Protection Level	IP21 (higher ratings are available on request)				
OPTIONAL FEATURES					
Parallel Operation	Up to 8 Units can be Connected in Parallel				
Remote Panel	LCD or Touchscreen Remote Panel Available on Request				
DIMENSIONS AND WEIGHT					
Size (WxDxH) [cm]	135x110x195			165x110x195	
Weight	740 kg	760 kg	850 kg	1550 kg	2100 kg

## General Features

Savior three-phase 3 level design Online UPS provides high efficiency, high reliability and precise control with low footprint. It is suitable for industrial equipment, hospitals, military and aviation, factories, data centers and telecom, civil and commercial buildings where high powered three-phase uninterrupted energy is needed.

Savior 3 Phase input, 3 Phase output UPS has industrial design with parallel operation up to 8 units, allowing to increase power or work redundant to increase protection of the load. Modbus and SNMP interface provides easy BMS and SCADA integration. Transformer-free design provides lighter and smaller solution.